






HR-0318VS	Technical Data		
	Max. Blind Rivet Setting Capacity (Head/Mandrel)	最大拉釘能力	5/32" (Alum. /Steel)
	Traction Power @ 90 PSIG	拉力	350 KgF
	Stroke Length	衝程	18 mm (11/16")
	Nosepieces Equipped	拉釘規格	2.4 mm (3/32")
			3.2 mm (1/8")
			4.0 mm (5/32")
Tool Weight	重量	1.30 Kg (2.86Lb)	
5/32" (4.0mm) Cap. Air-Hydraulic Riveter (VACUUM TYPE)			


HR-0618T	Technical Data		
	Max. Blind Rivet Setting Capacity (Head/Mandrel)	最大拉釘能力	3/16" (Steel / Steel)
	Traction Power @ 90 PSIG	拉力	596 KgF
	Stroke Length	衝程	18 mm (11/16")
	Nosepieces Equipped	拉釘規格	2.4mm (3/32")
			3.2 mm (1/8")
			4.0 mm (5/32")
4.8 mm (3/16")			
Tool Weight	重量	1.50 Kg (3.30 Lb)	
3/16" (4.8mm) Cap. Air-Hydraulic Riveter			

HR-0618VS	Technical Data		
	Max. Blind Rivet Setting Capacity (Head/Mandrel)	最大拉釘能力	3/16" (Steel / Steel)
	Traction Power @ 90 PSIG	拉力	596 KgF
	Stroke Length	衝程	18 mm (11/16")
	Nosepieces Equipped	拉釘規格	2.4mm (3/32")
			3.2 mm (1/8")
			4.0 mm (5/32")
4.8 mm (3/16")			
Tool Weight	重量	1.55 Kg (3.41 Lb)	
3/16" (4.8mm) Cap. Air-Hydraulic Riveter (VACUUM TYPE)			


HR-0918T	Technical Data		
	Max. Blind Rivet Setting Capacity (Head/Mandrel)	最大拉釘能力	3/16" (Steel / Steel)
	Traction Power @ 90 PSIG	拉力	900 KgF
	Stroke Length	衝程	18 mm (11/16")
	Nosepieces Equipped	拉釘規格	2.4mm (3/32")
			3.2 mm (1/8")
			4.0 mm (5/32")
4.8 mm (3/16")			
Tool Weight	重量	1.85 Kg (4.07 Lb)	
3/16" (4.8mm) Cap. Air-Hydraulic Riveter			

HR-0918VS	Technical Data		
	Max. Blind Rivet Setting Capacity (Head/Mandrel)	最大拉釘能力	3/16" (Steel / Steel)
	Traction Power @ 90 PSIG	拉力	900 KgF
	Stroke Length	衝程	18 mm (11/16")
	Nosepieces Equipped	拉釘規格	2.4mm (3/32")
			3.2 mm (1/8")
			4.0 mm (5/32")
4.8 mm (3/16")			
Tool Weight	重量	1.85 Kg (4.07 Lb)	
3/16" (4.8mm)Cap. Air-Hydraulic Riveter (VACUUM TYPE)			

HR-1214T	Technical Data		
	Max. Blind Rivet Setting Capacity (Head/Mandrel)	最大拉釘能力	3/16" All Materials 1/4" (Steel / Steel)
	Traction Power @ 90 PSIG	拉力	1200 KgF
	Stroke Length	衝程	14 mm (9/16")
	Nosepieces Equipped	拉釘規格	2.4mm (3/32")
			3.2 mm (1/8")
			4.0 mm (5/32")
4.8 mm (3/16")			
Tool Weight	重量	1.94 Kg (4.27 Lb)	
1/4" (6.4mm)Cap. Air-Hydraulic Riveter			

HR-1214VS	Technical Data		
	Max. Blind Rivet Setting Capacity (Head/Mandrel)	最大拉釘能力	3/16" All Materials 1/4" (Steel / Steel)
	Traction Power @ 90 PSIG	拉力	1200 KgF
	Stroke Length	衝程	14 mm (9/16")
	Nosepieces Equipped	拉釘規格	2.4mm (3/32")
			3.2 mm (1/8")
			4.0 mm (5/32")
4.8 mm (3/16")			
Tool Weight	重量	1.94 Kg (4.27 Lb)	
1/4" (6.4mm)Cap. Air-Hydraulic Riveter (VACUUM TYPE)			

HR-1819T	Technical Data		
	Max. Blind Rivet Setting Capacity (Head/Mandrel)	最大拉釘能力	1/4" All Materials
	Traction Power @ 90 PSIG	拉力	1800 KgF
	Stroke Length	衝程	19 mm (3/4")
	Nosepieces Equipped HR-1819-8VS (8.0 mm 5/16")	拉釘規格	4.8 mm (3/16")
			6.4 mm (1/4")
Tool Weight	重量	2.55 Kg (5.6 Lb)	
1/4" (6.4mm)Cap. Air-Hydraulic Riveter			

HR-1819-VS	Technical Data		
	Max. Blind Rivet Setting Capacity (Head/Mandrel)	最大拉釘能力	1/4" All Materials
	Traction Power @ 90 PSIG	拉力	1800 KgF
	Stroke Length	衝程	19 mm (3/4")
	Nosepieces Equipped	拉釘規格	4.8 mm (3/16")
			6.4 mm (1/4")
Tool Weight	重量	2.60 Kg (5.72 Lb)	
1/4"(6.4mm)Cap. Air-Hydraulic Riveter (VACUUM TYPE)			

HR-1017VSK	Technical Data	
Air-Hydraulic Blind Rivets Fastening Tool (1/4" Capacity)		
"PATENTED"		
		
Blind Rivet Setting Capacity: (Iron : 4.8 Aluminium : 6.4) All blind rivets and blind structural riveters up to & including 3/16" (4.8mm) diameter in all materials and 1/4" (6.4mm) diameter in coated carbon steel.		
Traction Power @90PSIG	拉力	1022KgF(2,248LbF)
Operating Air Pressure	使用壓力	6.3 Bar (90PSI)
Stroke Length	衝程	17mm (11/16")
Nosepieces Equipped	拉釘規格	2.4 mm (3/32")
		3.2 mm (1/8")
		4.0 mm (5/32")
		4.8 mm (3/16")
		6.4 mm (1/4")
Air Inlet Size	進氣口尺寸	1/4"NPT
Air Hose Size	進氣風管內徑	I.D.3/8"
Net Weight	淨重	1.95Kg